

TECHNICAL SPECIFICATIONS

AVAL, AVSHM Architectural vanity

CATALOG NUMBER _____
 TYPE _____
 DATE _____
 PREPARED BY _____
 PROJECT _____



HOUSING: Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. Knockouts provided on back.

DIFFUSER: The AV series include translucent faux alabaster acrylic fascias or white acrylic lenses with real wood, Shaker style fascias to create both up and down light components. Diffusers are attached to the housing with brass set screws for quick access.

ELECTRICAL: Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed.


MOUNTING: Flush horizontal wall mount.

AV Ordering Information

Series	Fascia	Lamps	Ballast	Voltage	Option
AV	AL = Alabaster	217 = (2) 17W 24" T8	B11 = Electronic T8	UNV = 120-277V	PSW = Pull Switch for on/off operation
	SHM = Maple	225 = (2) 25W 36" T8		120 = 120V	
	SHC = Cherry	232 = (2) 32W 48" T8		277 = 277V	
	SHMH = Mahogany				

For additional switching and wiring options, see Architectural Health Care unit (AW).

Dimensions



Lengths are 31", 43", 56"