

ASL
Aisle Lighter

CATALOG NUMBER _____
 TYPE _____
 DATE _____
 PREPARED BY _____
 PROJECT _____



Housing:

Die-formed heavy gauge steel with high-gloss, baked enamel finish over rust inhibiting phosphate coat. 7/8" knockouts provided for easy installation.

Reflector

Specular reflector manufactured from 95% reflective MIRO 4 aluminum in 4' sections to maximize light output and control beam spread.

Electrical

Fully wired for UNV 120-277V 50-60 Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed damp location.

Mounting

Aisle lighters can be surface, pendant or chain mounted depending on the application and desired mounting height.

ASL Ordering Information

Series	Length	#Lamps	Lamp Wattage/Type	Reflector
ASL	4 = 4'	1 = 1 lamp	28T5 = F28T5	W = White
	8 = 8'	2T = Tandem 2 lamps	54T5H = F54T5H0	S = Specular
			32T8 = F32T8	M4 = 95% reflective specular aluminum

Ballast	Voltage	Options
B11 = Electronic T8	U1 = 120 - 277V	ELS1 = Emergency Lighting (low lumens)
B11HP(x) = Electronic HPT8 (specify Ballast Factor: L = Low; N = Normal; or H = High)*	U3 = 347 - 480V	ELS2 = Emergency Lighting (medium lumens)
B12 = T5 Programmed Start	347 = 347V	ELS3 = Emergency Lighting (high lumens)
	480 = 480V	

*CEE Listed 4' HPT8 ballast

Dimensions

