

## AW Architectural Health Care



CATALOG NUMBER \_\_\_\_\_  
 TYPE \_\_\_\_\_  
 DATE \_\_\_\_\_  
 PREPARED BY \_\_\_\_\_  
 PROJECT \_\_\_\_\_

**HOUSING:** Heavy gauge steel with flush ends. KOs provided top, side and back. Baked white enamel over rust inhibiting phosphate coat, white interior.

**SHIELDING:** Snap-in D.R. acrylic diffuser for longer life and less breakage. Ribbed linear prisms for even light distribution. Translucent milk white is standard.

**OPTIONS:** White grounded 6' cordset, grounded convenience outlet, cool white lamp included, and rocker switch are available options.

**ELECTRICAL:** Fully wired for 120V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed.

Mounting: Individual or continuous rows.

### Architectural Health Care Ordering Information

Series	Fascia	# Lamps	Lamp type	Ballast	Switching**
AW	AL = Alabaster*	2	17 = 17W 24" T8	B11 = Electronic T8	For 3 lamp units
	SHM = Maple	3	25 = 25W 36" T8		Blank = dual ballasts
	SHC = Cherry		32 = 32W 48" T8		3L = (1) 3-lamp ballast
	SHMH = Mahogany				
					For 2 lamp units
					Blank = single ballast
					2/1L = (2) 1-lamp ballasts


\*Alabaster unit is ADA Compliant

\*\*For 4-way switching, dual ballasts are required.

Minimum quantities may apply. Contact factory.

Voltage	Options
UNV = 120-277V	LPSW = Less Pull Switch
120 = 120V	LNL = Less Night Light
277 = 277V	LCO = Less Convenience Outlet

### Dimensions



Lengths are 31", 43", 56"