



**Slimline and High Output Channels** are ideal for maximum illumination in retail stores and commercial environments. Available in 4', 6', and 8' individual lengths as well as continuous row mounting.

**Housing**

High-gloss, baked white enamel finish on steel housing with removable wireway access panel. Fixture is shipped fully wired and assembled. CHX models have patented (#4,422,132) flip-up socket bar and turn fastener for attaching wireway cover.

**Options**

Options include modular wiring, plug-in systems and wire guards.

**Electrical**

Fully wired for 120V, 60Hz operation with thermally protected, automatic resetting, Class P, high-power-factor ballast, unless otherwise specified. UL listed, damp location.

**Mounting**

Surface or pendant mount, high output model must be suspended at least 6" from ceiling for cooler operation.

**CHX Slimline And High Output Channel Ordering Information**

Series	# Lamps	Lamps	Options	Ballast
CHX	1	48 = 48"	<b>ELS1</b> = Emergency Lighting (low lumens) <b>ELS2</b> = Emergency Lighting (medium lumens) <b>ELS3</b> = Emergency Lighting (high lumens)	<b>B5</b> = Electronic T12
	2	72 = 72"		<b>HOB5</b> = High Output Electronic T12
	21 = Tandem, Two Lamps	96 = 96"		<b>B11</b> = Electronic T8 <b>HOB11</b> = High Output Electronic T8 <b>HO</b> = High Output <b>VHO</b> = Very High Output

Voltage	Options	Accessories
<b>UNV</b> = 120-277V <b>120</b> = 120V <b>277</b> = 277V	<b>6' CORD AND PLUG</b> <b>CPT(x)</b> 1 = 120V 2 = 277V <b>CP3</b> = Cord & Plug - 120V Straight Blade 5-15P  Plug-in Connectors <u>Ballast wired to Black:</u> <b>PL1</b> - one circuit, two wires <b>PL2 BK</b> - two circuits, three wires <u>Ballast wired to Red:</u> <b>PL2 RD</b> - two circuits, three wires	<b>CA24</b> = Chain Hanger Assembly - (2) 18" chains, (2) "V" hooks, (2) "S" hooks for total drop 24" <b>CS24</b> = "S" Hook (4) Chain Hanger Assembly (24" total drop) <b>PM(x)</b> = Pendant Mount, white stem - specify length in inches ( <b>24, 36, 48, 60, 72</b> ) <b>C</b> = Single white canopy (for use with pendant mount) <b>SN</b> = Snapper Brackets <u>Wire Guards</u> <b>WG230</b> = 36" (Order 2 for 72" units) <b>WG240</b> = 48" (Order 2 for 96" units)

**Dimensions**

