



IDP Industrial Decorative fixtures are ideal for spaces where a more refined look is desired. Finished end plates allow for attractive individual mounting.



Housing

Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. 7/8" knockouts provided for easy installation. Wired flip-up socket bars standard.

Reflector

Strong, rigid, die-formed white reflector in 4' sections. Optional perforated reflector for ambient uplight available.

Electrical

Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed.

Mounting

Surface mount or pendant mount with aircraft cable or stem/canopies. Individual mounting only.

IDP Industrial Decorative Ordering Information

Series	Lamps
IDP	232 = (2) 32W 48" T8

Ballast	Voltage	Accessories
B11 = Electronic T8 B11HP(x) = HPT8*	UNV = 120-277V	PM(x) = Twin Pendant Mount, 2 white stems - specify length in inches (24, 36, 48, 60, 72) CACC(xx) = Cable Kit, includes 2 cables, mounting hardware, white power cord and canopies; specify length in inches (48 or 72) C = Single white canopy

*CEE listed T8; specify (L)ow, (N)ormal, or (H)igh ballast factor. Contact factory for NEMA Premium.

Dimensions

