



IE Industrial Fluorescent models come standard with labor-saving pre-wired flip-up socket bars.



Housing

Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. 7/8" knockouts for easy installation.

Reflector

Strong, rigid, die-embossed solid white reflector in 4' sections, standard. Optional "A" apertures for 12% uplight.

Electrical

Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed damp location.


Mounting

Ceiling surface mount (*HO and VHO units must be suspended at least 6" from ceiling for cooler operation and longer ballast life*), spacing available with Snapper Bracket (SN), CA24 in kit or stem mount individual or continuous row. AC aligner clips available for continuous runs.

IE Industrial Ordering Information

Series	# Lamps	Lamps	Reflector Options
IE	1	28 = 28W 48" T5	<i>Solid is standard</i> A = Aperture 12% uplight
	2	32 = 32W 48" T8	
	3	48 = 48" Slimline	
		96 = 96" Slimline	
	21 = Tandem, 2 lamps	<i>High Output</i>	
	22 = Tandem, 4 lamps	48 = 48" HO	
	23 = Tandem, 6 lamps	54 = 54W T5HO	
		96 = 96" HO (1 or 2 lamp only)	
		<i>Very High Output</i>	
		48 = 48" VHO (1 or 2 lamp only)	
	96 = 96" VHO (1 or 2 lamp only)		

Dimensions



Options	Ballast	Switching	Voltage
ELS1 = Emergency Lighting (low lumens)	B5 = Electronic T12	<i>For 2 lamp units</i>	UNV = 120-277V 120 = 120V 277 = 277V
ELS2 = Emergency Lighting (medium lumens)	HOB5 = High Output Electronic T12	<i>Blank = single ballast</i>	
ELS3 = Emergency Lighting (high lumens)	B11 = Electronic T8	2/1L = (2) 1-lamp ballasts	
	B11HP(x) = HPT8*	<i>For 3 and 4 lamp units</i>	Blank = dual ballasts 3L = (1) 3-lamp ballast 4L = (1) 4-lamp ballast
	HOB11 = High Output Electronic T8	<i>For 6 lamp tandem units</i>	
	B12 = Electronic T5	2/3L = (2) 3-lamp ballasts	
	HO = High Output	2L4L = (1) 2-lamp and (1) 4-lamp ballast	
	VHO = Very High Output		

*CEE listed T8; specify (L)ow, (N)ormal, or (H)igh ballast factor. Contact factory for NEMA Premium.

Accessories

- SN - Snapper Brackets
- CA24 - Chain Hanger Assembly (24" total drop)
- CS24 - "S" Hook (4) Chain Hanger Assembly (24" total drop)
- HKSC - Hook & Chain Assembly (24" total drop; 4' fixtures only)
- LG48 - 48" wire guard
- AC - Aligner Clip
- CHJ - Housing Joiner