

Optional reflector end, RE

Simkar IF Premium Turret Industrial specification-grade fixtures feature spring-loaded lamp holders to provide positive lamp contact and retention.



Housing

Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. 7/8" knockouts for easy installation. Two-lamp model has 6" on-center lamp spacing.

Reflector

Heavy gauge, rigid, die-embossed reflector with transverse beads, in 4' sections; high-gloss white reflector, or optional "A" apertures for 15% uplight. High reflectance specular aluminum insert (SR) available.

Electrical

Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard (except Slimline and HO models) unless otherwise specified. UL listed damp location.




Mounting

Ceiling surface mount (HO and VHO units must be suspended at least 6" from ceiling for cooler operation and longer ballast life), spacing available with Snapper Bracket (SN), CA24 chain kit or stem mount individual or continuous row.

IF Premium Turret Industrial Ordering Information

Series	# Lamps	Lamps	Reflector Options
IF	2	28 = 28W 48" T5	A = Aperture, 15% uplight
	3	32 = 32W 48" T8	
	4	48 = 48" Slimline	
	22 = Tandem, 4 lamps	96 = 96" Slimline	
	23 = Tandem, 6 lamps	<u>High Output</u>	
	24 = Tandem, 8 lamps	48 = 48" HO	
		54 = 54W T5HO	
		96 = 96" HO	
		<u>Very High Output</u>	
		48 = 48" VHO	
	96 = 96" VHO		

Dimensions



Options	Ballast	Switching	Voltage
SR = Specular Reflector	B5 = Electronic T12	<i>For 2 lamp units</i>	UNV = 120-277V 120 = 120V 277 = 277V
ELS1 = Emergency Lighting (low lumens)	B11 = Electronic T8	Blank = single ballast	
ELS2 = Emergency Lighting (medium lumens)	B11HP(x) = HPT8*	2/1L = (2) 1-lamp ballasts	
ELS3 = Emergency Lighting (high lumens)	HOB11 = High Output Electronic T8	<i>For 3 and 4 lamp units</i>	Blank = dual ballasts 3L = (1) 3-lamp ballast 4L = (1) 4-lamp ballast
	B12 = Electronic T5	Blank = single ballast	
	HO** = High Output	2/3L = (2) 3-lamp ballasts	
	VHO** = Very High Output	2L/4L = (1) 2-lamp and (1) 4-lamp ballast	

*CEE listed T8; specify (L)ow, (N)ormal, or (H)igh ballast factor. Contact factory for NEMA Premium.

** Must be spaced at least 6" from ceiling

Options	Accessories
CORD AND PLUG	RE = Reflector end
CPT(x) (twist + lock)	WG = Wire Guards (page 93)
1 = 120V	IF JOINER = For continuous run
2 = 277V	
CP3 = Cord & Plug - 120V Straight Blade 5-15P	