



OV410 Enclosed gasketed fixture is equipped with a pressure-lock cam latch to tightly seal out vapor, moisture and dust. Available in 4' and 8' lengths as well as T8, T12, and high output.



Dimensions



Two Light



Four Light

Housing

Heavy-gauge steel with welded corners and compressible gasketing. KOs provided top and ends.

Shielding

Standard with clear acrylic prismatic lens.

Options

Popular options include wet location label (suffix WL) for ceiling mount only (includes RTV silicone seal).

Electrical

Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified (except HO models). U.L. listed.

Mounting

Surface or stem, individual or continuous rows.

OV410 Gasketed Striplite Ordering Information

Series	# Lamps	Lamp Type	ELS Options
OV410	2	32 = 32W 48" T8	ELS1 = Emergency Lighting (low lumens)
	4	48 = 48" T12 HO	ELS2 = Emergency Lighting (medium lumens)
	22 = Tandem, 4 lamps	96 = 96" T8/T12 Slimline / HO	ELS3 = Emergency Lighting (high lumens)

Ballast	Switching	Voltage	Options
B5 = Electronic T12	FOR 2 LAMP UNITS	UNV = 120-277V	WL = Wet Location (Ceiling mount only)
B11 = Electronic T8	Blank = single 2-lamp ballast (standard)	120 = 120V	FB* = Lay-in Fast-Blow Fusing
B11HP(x) = HPT8*	2/1L = (2) one-lamp ballasts	277 = 277V	SB* = Lay-in Slow-Blow Fusing
HO = High Output	FOR 4 LAMP UNITS		
	Blank = (2) 2-lamp ballasts		
	4L = (1) 4-lamp ballast		

*CEE listed T8; specify (L)ow, (N)ormal, or (H)igh ballast factor. Contact factory for NEMA Premium.