


CATALOG NUMBER _____
 TYPE _____
 DATE _____
 PREPARED BY _____
 PROJECT _____

SLP Low Profile Residential



HOUSING: Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. Ends are hand finished to a stainless steel look. Inside is grooved to accept acrylic lens and avoid light loss.

SHIELDING: Smooth milk white formed acrylic.

ELECTRICAL: Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A electronic ballast as standard unless otherwise specified. UL listed.

MOUNTING: Flush mounted or pendant hung with CACC Suspension Kit. CACC Suspension Kit includes white cord, white canopies and 1/16" aircraft cable. Individual mounting only.

SLP Series Ordering Information

Series	Ends	Lamps	Ballast	Voltage
SLP	M = Brushed metal	217 = (2) 17W 24" T8	B11 = Electronic T8	UNV = 120-277V
	W = White	232 = (2) 32W 48" T8	B22 = LPF T8/T12	120 = 120V 277 = 277V*

*B11 only

Accessories

CACC(xx)* = Cable Kit, includes 2 cables, mounting hardware, white power cord and canopies; specify length in inches (**48** or **72**)

Dimensions

