



- Shallow 3-1/4" depth is ideal for low ceilings.
- V-shaped acrylic diffuser distributes light evenly and reduces glare.
- Lift and shift lens hinges from either side for easy, tool-free cleaning and relamping.
- Solid oak ends (WRCO) add a decorative touch.
- Die-formed, heavy gauge, steel housing.
- Flush, ceiling mount – stem, individual or continuous row.
- U.L. listed.

Electrical

Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed damp location.



Available with a glare-reducing diffuser, Wraparounds can be individually or continuous-row mounted. Non-yellowing acrylic prismatic lens keeps the light bright.



Commercial Wraparounds Ordering Information

Series	Lamps	Ballast	Switching	Voltage
SY920	217 = (2) 17W 24" T8 232 = (2) 32W 48" T8 332 = (3) 32W 48" T8 417 = (4) 17W 24" T8 432 = (4) 32W 48" T8	B11 = Electronic T8	FOR 3 AND 4 LAMP UNITS Blank = dual ballasts 3L = (1) 3-lamp ballast 4L = (1) 4-lamp ballast	UNV = 120-277V 120 = 120V 277 = 277V

Residential Wraparounds Ordering Information

Series	Lamps	Ballast	Voltage
WRW = White ends WRCO = Oak ends	217 = (2) 17W 24" T8 24 = (2) 34/40W 48" T12 417 = (4) 17W 24" T8 44* = (4) 34/40W 48" T12	B22 = LPF T8/T12 120V	120 = 120V

*Dual ballasts required

Dimensions

