



**Housing**

Heavy gauge steel with high-gloss baked "safety" yellow enamel finish over rust inhibiting phosphate coat. Single strut (SKDL) mounting arm units are equipped with a folding knuckle joint allowing for horizontal and vertical adjustment. Double strut (SKDDL) mounting arm units provide greater strength and durability. All units supplied with lightweight, corrosion resistant polycarbonate lamp head.

**Electrical**

6' 120V 18-3 cord, plug, and rocker switch supplied. UL listed.

**Mounting**

Horizontal mount. Two piece wall mounting bracket provided.

The docklight series uses polycarbonate heads for resistance to dents, breaks and stays cool to the touch. Double strut arms (SKDDL) on the HID model provides sturdy, durable construction. High pressure sodium option is available for long lamp life and lower starting temperature.

**SKDL and SKDDL Series Ordering Information**

Series	Lamp	Arm Length*	Lamp Head
SKDL = Single strut SKDDL = Double strut	HPS = 50W High pressure sodium (Leave blank for R40 or PAR38 150W max)	40 = 40" 60 = 60"	P = Polycarbonate

\*For 24" or 90" arm lengths contact factory.

**Accessories**

**SKWG8P** = Stainless steel wireguard to protect lamp. Mounts easily to holes provided in polycarbonate lamp head.  
**SKDLFAN\*** - Fan

**Replacement Lamp Heads**

**SKINC-HEAD** = For incandescent models  
**SKHPS-HEAD** = For high pressure sodium models

\*Available with SKDDL, double strut only. Lamp provided.

**Dimensions**

