



SP175

SP175 Smooth White acrylic Wraparound is available in single-lamp, 2', 3', 4' and 8' tandem T8. Unit is dust proof and suitable for wall mount.



Housing

Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. Knockouts provided.

Shielding

Milk white acrylic.

Electrical

Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed damp location.

Mounting

Individual or continuous row. Stem or surface mount. Order accessory CR-SP175 for continuous row mounting.

SP175 Series Ordering Information

Series	# Lamps	Lamps
SP175	1 21 = Tandem, 2 Lamps (32W only)	17 = 17W 24" T8 25 = 25W 36" T8 32 = 32W 48" T8

ELS Option	Ballast	Voltage
ELS1 = Emergency Lighting (low lumens) ELS2 = Emergency Lighting (medium lumens) ELS3 = Emergency Lighting (high lumens)	B11 = Electronic T8 B11HP(x) = HPT8*	UNV = 120-277V 120 = 120V 277 = 277V

*CEE listed T8; specify (L)ow, (N)ormal, or (H)igh ballast factor. Contact factory for NEMA Premium.

Accessories
PM(x) = Pendant Mount, white stem - specify length in inches (24, 36, 48, 60, 72) C = Single White Canopy CR-SP175 = Continuous row mounting band

Dimensions

