



**SY130 Clear Prismatic Flat Lens Narrow Wraparound** is available in single-lamp 2', 3', 4' and 8' tandem. A two-lamp model is available in 2', 4' and 8' tandem T5 and T8. SY130 is intended for ceiling mount applications.



**Housing**

Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. Knockouts provided.

**Shielding**

Clear DR acrylic prismatic lens for improved impact resistance.

**Electrical**

Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed damp location.

**Mounting**

Individual or continuous row stem or surface mount. Only one CR band supplied with every tandem unit. For continuous row mounting, additional CR bands are needed.

**SY130 Series Ordering Information**

| Series | # Lamps              | Lamps                                | Options  |
|--------|----------------------|--------------------------------------|--|
| SY130  | 1                    | 14 = 14W 24" T5                      | ELS1 = Emergency Lighting (low lumens)<br>ELS2 = Emergency Lighting (medium lumens)<br>ELS3 = Emergency Lighting (high lumens) |
|        | 2                    | 17 = 17W 24" T8                      |  |
|        | 21 = Tandem, 2 lamps | 24 = 24W 24" T5HO                    |  |
|        | 22 = Tandem, 4 lamps | 25 = 25W 36" T8                      |  |
|        |                      | 28 = 28W 48" T5                      |  |
|        |                      | 32 = 32W 48" T8<br>54 = 54W 48" T5HO |  |

| Ballast                                 | Voltage                                    | Accessories   |
|---|--|---|
| B11 = Electronic T8<br>B11HP(x) = HPT8* | UNV = 120-277V<br>120 = 120V<br>277 = 277V | PM(x) = Pendant Mount, white stem - specify length in inches (24, 36, 48, 60, 72)<br>C = Single White Canopy<br>CR = Continuous row mounting band |

\*CEE listed T8; specify (L)ow, (N)ormal, or (H)igh ballast factor. Contact factory for NEMA Premium.

**Dimensions**

