



TE3P Parabolic

TE3P Parabolic is a shallow plenum parabolic specifically designed to provide exceptional visual comfort. Its low brightness and overall photometric performance comply with IES RP-1. The TE3P is only 3 3/4" high and can be installed in NEMA type "F" or "G" ceilings.




Housing

Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. Knockouts and/or access plate provided.

Shielding

Excellent VCP; meets IES RP-1. Low iridescence, anodized semi-specular or specular aluminum parabolic louver is installed in flush steel door frame (black) with mitered corners that can be hinged from either side. Swing-action cam latches provide positive fit. Light traps standard. High-reflectance white reflector standard.



A low-iridescence, semi-specular 57-cell louver is standard; specular aluminum is optional. Louvers are installed in a flush, black steel door to create an attractive floating appearance. The door hinges from either side with a swing-action cam latch for easy relamping.

Electrical

Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed.

Mounting

Lay-in (T) or Flange (F) troffer with access plate provided with 2 KOs and ground screw. 2 x 2 and 2 x 4 flanged fixtures require field assembly. Optional EC515 Earthquake Clip for lay-in grid ceilings. Specify FE3P for flange unit or use GCK kit. (see page 91) Flanged units require field assembly.



TE3P Series Ordering Information

Series	Spec Door	Size	Lamps	Cell Config/3 Rows
TE3P = Lay-in FE3P = Flange	Black steel, standard WF = Flat steel, white	242 = 2 x 2 244 = 2 x 4	317 = (3) 17W 24" T8 332 = (3) 32W 48" T8	27C = 27 cell semi-Specular (2x2) 27CS = 27 cell specular (2x2) 57C = 57 cell semi-Specular (2x4) 57CS = 57 cell specular (2x4)

Options	Ballast	Switching	Voltage
SR = Specular Reflector ELS1 = Emergency Lighting (low lumens) ELS2 = Emergency Lighting (medium lumens) ELS3 = Emergency Lighting (high lumens)	B11 = Electronic T8 B11HP(x) = HPT8* D = Dimming (specify ballast)	Blank = dual ballasts (2x4 only) 3L = (1) 3-lamp ballast	UNV = 120-277V 120 = 120V 277 = 277V 347 = 347V

*CEE listed T8; specify (L)ow, (N)ormal, or (H)igh ballast factor. Contact factory for NEMA Premium.

Dimensions



Options	Accessories
L = Lamps Installed (Specify Lamps) FL4 = 3/8", 6' flex with two #18, one ground and two connectors FL5 = 3/8", 6' flex with three #18, one ground and two connectors M = Master; includes 9' intertie and snap-in connector S = Satellite; includes snap-in connector FB = Fast Blow Fuse SB = Slow Blow Fuse BP = Bulk Pack	EC515 = Earthquake Clip (Specify FEP for flange unit or use GCK kit) GCK (Grid Conversion Kits) GCK 22 = 2' x 2' GCK 24 = 2' x 4'