


# TECHNICAL SPECIFICATIONS

**TWW**

**Lay-in wall washer**

CATALOG NUMBER \_\_\_\_\_  
 TYPE \_\_\_\_\_  
 DATE \_\_\_\_\_  
 PREPARED BY \_\_\_\_\_  
 PROJECT \_\_\_\_\_



**Housing:** Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. Access plate (topside) provided with two KOs and ground screw.

**Reflector:** Downward throw asymmetric reflector with semi-specular finish offers high optical performance, producing even light to vertical surface from single twin-tube lamp.

**Electrical:** Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise specified. UL listed.

**Mounting:** Recommended mounting position 36" from wall. Includes integral hang tabs. Offset ends for continuous row mounting.

## TWW Series Ordering Information

Series	Size	Lamps	Ballast	Voltage
TWW	82 = 8" x 2'	140 = (1) 40W 22 1/2" twin tube (2' model)	B14 = Electronic TT	UNV = 120-277V
	84 = 8" x 4'	240 = (2) 40W 22 1/2" twin tube (4' model)		120 = 120V
		250 = (2) 50W 22 1/2" twin tube (4' model)		277 = 277V

## Dimensions

