


CATALOG NUMBER _____
 TYPE _____
 DATE _____
 PREPARED BY _____
 PROJECT _____

V1000 Vandal Resistant



HOUSING: Marine Grade A, heavy-gauge aluminum with gasketing for maximum corrosion resistance. Models with painted parts receive high-gloss baked enamel applied after pre-treatment to ensure superior paint adhesion and rust resistance. Incandescent and Compact fluorescent fixtures have white housings.

SHIELDING: High-impact, UV Treated, clear prismatic polycarbonate for remarkable impact strength.

ELECTRICAL: Incandescent fixtures have medium base socket. Fluorescent models are wired for 120V, 60Hz operation. HID model available.

MOUNTING: Ceiling Mount.

V1000 Series Ordering Information

Series	Lamp Type	Housing
V10	00 = (2) 60W A19 18 = (2) 9W CFL 26 = (2) 13W CFL 26Q = (1) 26W Quad 52Q = (2) 26W Quad <i>For HID model, see GCS</i>	A = Aluminum (standard)

Voltage	Options	Accessories
UNV = 120-277V 120 = 120V 277 = 277V	MS = Maximum Security (Tamperproof screws) L1 = Lamps	V101A = Aluminum back box for 1/2" conduit, white TSD = Tamper-proof screwdriver