


TECHNICAL SPECIFICATIONS

V5000 Vandal resistant



CATALOG NUMBER _____
 TYPE _____
 DATE _____
 PREPARED BY _____
 PROJECT _____

Housing: Marine Grade A heavy-gauge aluminum with gasketing for maximum corrosion resistance. Models with painted parts receive high-gloss baked enamel applied after pre-treatment to ensure superior paint adhesion and rust resistance. Fixture housing is white. V501A aluminum back box has a white finish.

Shielding: High-impact polycarbonate for remarkable impact strength.

Electrical: Incandescent fixtures have medium base socket. Fluorescent models are wired for 120V, 60Hz operation. UL listed, wet location: 60W max., damp location: ceiling - 60W max., wall - 75W max.

Mounting: Incandescent base up wall mount. See individual models for ratings for ceiling mount.

V5000 Series Ordering Information

Series	Lamp Type	Housing	Voltage
V50	00 = (1) 60W or 75W A19	A = Aluminum (standard)	120 = 120V
	07 = (1) 7W CFL		277* = 277V
	14 = (2) 7W CFL		

*Back box may be required for 277V models

Options	Accessories
MS = Maximum security (Tamperproof screws)	V501A = Aluminum back box for 1/2" conduit, white
W = White polycarbonate lens	TSD = Tamper-proof screwdriver
L1 = Lamps	

Dimensions

