


# TECHNICAL SPECIFICATIONS

## V6000 Vandal resistant



CATALOG NUMBER \_\_\_\_\_  
 TYPE \_\_\_\_\_  
 DATE \_\_\_\_\_  
 PREPARED BY \_\_\_\_\_  
 PROJECT \_\_\_\_\_

**HOUSING:** Marine Grade A heavy-gauge aluminum with gasketing for maximum corrosion resistance. Models with painted parts receive high-gloss baked enamel applied after pre-treatment to ensure superior paint adhesion and rust resistance. Fixture housing is white. All units are Maximum Security (tamperproof screws).

**SHIELDING:** High-impact polycarbonate for remarkable impact strength.

**ELECTRICAL:** Incandescent fixtures have medium base socket. Fluorescent models are wired for 120V, 60Hz operation. UL listed, wet location.

**MOUNTING:** Incandescent base up wall mount. See individual models for ratings for ceiling mount.

### V6000 Series Ordering Information

Series	Lamps	Housing	Voltage
V6	009 = (1) 9W CFL	A = Aluminum (standard)	120 = 120V
	018 = (2) 9W CFL		277 = 277V
	013 = (1) 13W CFL		
	026 = (2) 13W CFL		
	018Q = (1) 18W Quad		
	100 = Max 100W A		

Options	Accessories
MS = Maximum security (Tamperproof screws)	TSD = Tamper-proof screwdriver
L1 = Lamp	

### Dimensions

